

FICHE TECHNIQUE

Sparkos


→ Fontaine osmoseur : eau froide, chaude, ambiante, et pétillante

CHARACTERISTICS

COLD WATER	5 l/h
HOT WATER	5 l/h
WATER WITH GAS	5 l/h
CAP. COLD WATER TANK	2 liters
CAP. HOT WATER TANK	Tankless, instantaneous heating.
CAP. CARBONATING RESERVOIR	1 liter
REFRIGERATION SYSTEM	Heat pump. Cooling in tank.
COMPRESSOR POWER	70 W
REFRIGERANT GAS	R600a
COLD WATER TEMPERATURE	5°C - 10°C
HEATING POWER	2100 W
CUSTOMER WATER TEMPERATURE	45°C - 85°C
GERMICIDAL SYSTEM	UV led lamp inside the tank and at water outlets.
LEAKAGE PROTECTIONS	AQUASTOP leak sensor included
MEMBRANE FLUSHING	Includes automatic membrane flushing to extend membrane life.
INLET WATER PRESSURE (MAX-MIN)	3 - 1 BAR
INLET WATER TEMPERATURE (MAX-MIN)	38°C - 5°C
CONNECTIONS	1/4" inlet- 1/4" drain
WEIGHT	18,5 KG



-  TACTILE PUSH BUTTONS
-  INDICATOR OF TEMPERATURES
-  FAST CONNECTIONS AND MAXIMUM SECURITY
-  FORCED VENTILATION SYSTEM
-  DESKTOP UNIT



WLG (B-60326279), is member of the Water Quality Association.



ACCREDITED BY ENAC
Certif. n° 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 for WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs to Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.